

MP-30 Payphone

- Suitable for outdoor areas
- Coin operated
- Graphic display with 4 soft keys
- Flexible functionality
- Software download



Siemens Payphones

www.siemens.com.au/payphones

SIEMENS

MP-30 Payphone



Features

- Suitable for outdoor use
- User-friendly interface, with large display and soft keys
- Flexible functionality using programmable parameters
- Software downloading capability
- V22.bis modem for connection to QP-SETM management system at 2,400 bps
- 50Hz or 12KHz pulse charging
- Polarity reversal detection
- 4 function keys
- 4 programmable soft key for quick access to services
- 128 x 64 pixel graphic display with back light.

Coin system

- Accepts 10c, 20c, 50c, \$1 and \$2 coins
- Timed local calls (optional)
- Coin release button
- Fast power-efficient 8-position intermediate coin storage (escrow)
- Internal coin box with separate key

Security features

- Advanced fraud detection algorithms
- Strong 2-mm thick steel door
- 6-mm thick tough polycarbonate display protection
- Tough ergonomic ABS plastic handset with armoured cord
- Metal alloy keypad

Maintenance characteristics

- Full diagnostic and test capabilities
- Menu-driven program for field maintenance
- Display of alarms, parameters, statistics and faulty modules using the payphone test-menu
- Modular internal construction
- Remote diagnostics option from Siemens QP-SETM management system
- Failure clearance reports (option)
- Only standard tools are required

Management system access (option)

- Payphones administered by the Siemens QP-SETM management system
- Flexible functionality, creation and modification of parameters
- Fast efficient software and parameter downloading with programmable software activation date
- Payphone data recording – traffic, call registers, coin collections and alarms

Other characteristics

Telephone interface

- Standard 2-wire analogue PSTN interface

Power Supply

- Line-powered payphone

Operating environment

- Coated electronics
- Temperature range: -10°C to +60°C
- Relative humidity: up to 95% without condensation at 40°C

Key Pad

- 12-key alphanumeric Australian standard
- 4 function keys
- 4 keys, alongside the graphic display, programmable from the QP-SETM management system

Display

- 128 x 64 pixel graphic LCD, up to 4 lines x 20 characters
- Back light

Handset

- Magnetic hookswitch

Dimensions

- Height: 360mm
- Width: 280mm
- Depth: 270mm
- Weight: 13.5Kg

For more information please contact Siemens on 1800 633 422,
via Fax (02) 9491 5454 or via email PP_Info.au@siemens.com